

PRODUCT NAME: **JSR NFR016D2-55cP**

SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: **JSR NFR016D2-55cP**
General Use: Photoresist for Integrated Circuit Production
Product Description: Photosensitizer and Phenolic Resin Solution

MANUFACTURER:
JSR Corporation
1-9-2, Higashi-Shinbashi,
Minato-ku, Tokyo
105-8640 Japan

EMERGENCY TELEPHONE NUMBERS:
CHEMTREC: +1-800-424-9300
(in USA) 24Hrs Every day
Telephone: +81-3-6218-3592
9:15-17:45 Jpn M-F
Facsimile: +81-3-6218-3692
24Hrs Every day

DISTRIBUTOR:
JSR Micro Inc.
1280 North Mathilda Ave.,
Sunnyvale, CA 94089
Telephone: +1-408-543-8800

2. HAZARDS IDENTIFICATION

GHS Classification





Hazard Group	Hazard class	Category	
Physical Hazards	Explosives	Not Classified	
	Flammable gases	Not Classified	
	Flammable aerosols	Not Classified	
	Oxidizing gasses	Not Classified	
	Gases under pressure	Not Classified	
	Flammable liquids	Category 3	
	Flammable solids	Not Classified	
	Self-reactive substances and mixtures	Not Classified	
	Pyrophoric liquids	Not Classified	
	Pyrophoric solids	Not Classified	
	Self-heating substances and mixtures	Not Classified	
	Substances and mixtures which, in contact with water, emit flammable gases	Not Classified	
	Oxidizing liquids	Not Classified	
	Oxidizing solids	Not Classified	
	Organic peroxides	Not Classified	
Corrosive to metals	Not Classified		
Health Hazards	Acute toxicity	Oral	Not Classified
		Dermal	Not Classified
		Inhalation (Gasses)	Not Classified
		Inhalation (Vapors)	Category 3
		Inhalation (Dusts and Mists)	Not Classified
	Skin corrosion/irritation	Category 2	
	Serious eye damage/eye irritation	Category 2	
	Respiratory or skin sensitization	Not Classified	
Germ cell Mutagenicity	Not Classified		
Carcinogenicity	Not Classified		

PRODUCT NAME: **JSR NFR016D2-55cP**

	Reproductive toxicity	Category 2
	Specific target organ systemic toxicity-Single exposure	Category 1
	Target Organs	Nervous system
	Specific target organ systemic toxicity-Repeated exposure	Not Classified
	Target Organs	NA
	Aspiration hazard	Not Classified
Hazardous to the aquatic environment	Acute aquatic toxicity	Not Classified
	Chronic aquatic toxicity	Not Classified

GHS label elements

Hazard symbols:

Flame	Skull and crossbones	Exclamation mark	Health Hazard	
				

Signal word: **Danger**

Hazard statement:

- Flammable liquid and vapor.
- Toxic if inhaled.
- Causes skin irritation.
- Causes serious eye irritation.
- Suspected of damaging fertility or the unborn child.
- Causes damage to the central nervous system and respiratory system.

Precautionary Statements:

Prevention:

- Keep away from heat, sparks, open flames and hot surfaces. – No smoking.
- Keep container tightly closed.
- Ground/Bond container and receiving equipment.
- Use explosion proof electrical, ventilation, lighting and equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Wear protective gloves, protective clothing, eye protection and face protection.
- Do not breathe dust, fumes, gas, mist, vapors or spray.
- Use only outdoors or in a well ventilated area.
- Wash hands thoroughly after handling.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Do not eat, drink or smoke when using this product.

Response:

- If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower.

PRODUCT NAME: **JSR NFR016D2-55cP**

- In case of fire: Use carbon dioxide, alcohol foam or dry chemical to extinguish.
- If inhaled: Remove person to fresh air and keep comfortable for breathing.
- Call a poison center, doctor or seek medical attention if you feel unwell.
- Specific treatment (see section 4 on this SDS).
- If skin irritation occurs: Get medical advice/attention.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.
- If exposed or concerned: Call a poison center or doctor. Get medical advice/attention.

Storage:

- Store in a well ventilated place. Keep container tightly closed. Keep cool.
- Store locked up.

Disposal:

- Dispose of contents/containers in accordance with local and federal regulations.

NFPA RATING (Scale 0 – 4): HEALTH = 1, FIRE = 2; REACTIVITY = 0

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	%	CAS No.
Phenolic resin	20-30	Proprietary
Trisphenol derivative	1-10	Proprietary
Melamine compound	1-10	Proprietary
Photosensitizer	Less than 3	Proprietary
Methyl 3-methoxypropanoate (MMP)	55-65	3852-09-3

*Note- The specific chemical identity and exact percentage of composition of some ingredients have been withheld as a trade secret.

4. FIRST AID MEASURES

INHALATION:

May cause irritation to nose and throat. Remove exposed person to fresh air; perform artificial respiration if necessary.

EYE CONTACT:

Eye contact may cause irritation and corneal injury. Immediately flush eyes with plenty of water at least 15 min. Call a physician.

SKIN CONTACT:

Prolonged and repeated contact with skin may cause irritation and dermatitis. Flush skin with water and soap.

INGESTION:

Swallowing may cause nausea and pain in esophagus and stomach. Give large quantities of water, contact a poison center and call physician immediately.

NOTE TO PHYSICIAN:

Treatment may vary with condition of victim and specifics of incident.

5. FIRE-FIGHTING MEASURES

GENERAL HAZARD:

Combustible liquid. May release vapors that form flammable mixtures when temperatures are at or above the flash point. Toxic gases will form upon combustion.

PRODUCT NAME: **JSR NFR016D2-55cP**

EXTINGUISHING MEDIA:

Carbon dioxide, alcohol foam or dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES:

Water should be used to keep fire exposed containers cool and to disperse vapors. Firefighters should wear self-contained breathing apparatus.

FIRE AND EXPLOSION HAZARDS:

Combustible liquid. Toxic gases, smoke, and oxides of carbon will form upon combustion.

6. ACCIDENTAL RELEASE MEASURES

LARGE SPILL/SMALL SPILL:

For indoor spills, provide increased ventilation as required to minimize exposure. Contain, absorb, and cleanup the spill as indicated in the appropriate land or water section below. Dispose of absorbent and other waste in an appropriate chemical waste container. Wear proper personal protective equipment. Wash thoroughly after handling.

LAND SPILL:

Dike or absorb with inert absorbent material and transfer to D.O.T. container for disposal.

WATER SPILL:

Remove from surface by skimming or with suitable absorbent.

7. HANDLING AND STORAGE

GENERAL:

Store in original container in a dry area. Avoid heat, sunlight, and ignition sources. Open only under safe light and well ventilated conditions. Loosen closure cautiously before opening. When using this substance: (a) avoid breathing the substance; (b) avoid ingestion; (c) use respiratory protection when in dust or mist form. Wear chemical goggles, resistant gloves and protective clothing to prevent contact. Wash thoroughly after handling.

RECOMMENDED STORAGE TEMPERATURE:

Maintain the storage temperature below 35°C (95°F). This storage temperature is intended for health and safety purposes only and is valid within the shelf life + 3 month period. For technical applications, see the product specifications and label.

STORAGE PRESSURE:

Atmospheric

INCOMPATIBILITIES:

Strong oxidizing agents, strong acids, strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

The use of local exhaust ventilation is recommended to control emissions near the source. Laboratory samples should be handled in a fumehood. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Under conditions of frequent use or heavy exposure, respiratory protection may be needed. Respiratory protection is ranked in order from minimum to maximum. Consider warning properties before use. NIOSH approved respirators as follows:
Any chemical cartridge respirator with organic vapor cartridge(s).
Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).

PRODUCT NAME: **JSR NFR016D2-55cP**

Any air-purifying respirator with a full facepiece and an organic vapor canister.
For Unknown Concentrations or Immediately Dangerous to Life or Health.
Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply.
Any self-contained breathing apparatus with a full facepiece.

SKIN PROTECTION:

Wear impermeable gloves and clothing during activities where there is potential for direct skin contact with chemical.

EYE PROTECTION:

Wear primary eye protection such as splash resistant safety goggles with a secondary protection faceshield. Provide an emergency eye wash station and quick drench shower in the immediate work area.

EXPOSURE GUIDELINE (S):

OSHA HAZARDS (29 CFR 1910.1200) Exposure Limits 8 hrs. TWA (ppm)

COMPONENT	OSHA PEL	ACGIH TLV
Phenolic resin	Not established	Not established
Trisphenol derivative	Not established	Not established
Melamine compound	Not established	Not established
Photosensitizer	Not established	Not established
MMP	Not established	Not established

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Value
Appearance:	Clear and pale yellow liquid
Odor:	Sweet, Ester-like
Odor threshold:	No applicable information available
Vapor Pressure:	2.4 hPa at 20 °C
Relative Density:	0.9 - 1.1
Solubility:	Moderate in water
Boiling Point:	145 °C 293 °F
Flashpoint and Method:	47 °C (est.) 117 °F (est.)
Flammable Limits:	1.9 % LEL 13.1 % UFL

Properties	Value
Autoignition Temperature:	389 °C 732.2 °F
pH:	No applicable information available
Melting/Freezing Point:	NA °C NA °F
Evaporation rate:	No applicable information available
Flammability:	Category 3
Vapor Density:	No applicable information available
Decomposition Temperature:	NA °C NA °F
Partition coefficient:	No applicable information available
Viscosity:	No applicable information available

10. STABILITY AND REACTIVITY

PRODUCT NAME: **JSR NFR016D2-55cP**

POSSIBILITY OF HAZARDOUS REACTIONS:

May react with strong oxidizing agents, strong acids, and strong bases.

CHEMICAL STABILITY:

Materials containing similar structural groups are normally stable. This material maybe sensitive to peroxide formation.

CONDITIONS TO AVOID:

Avoid heat, sunlight and ignition sources.

INCOMPATIBLE MATERIALS:

Strong oxidizing agents, strong acids, strong bases.

HAZARDOUS DECOMPOSITION PRODUCTS:

Combustion will produce toxic vapors and gases.

11. TOXICOLOGICAL INFORMATION

SOLVENT (MMP):

ACUTE TOXICITY

Oral LD50 Rat 3,700 mg/kg

Inhalation LC50 Rat 5.8 mg/L

(Vapor)

MUTAGENICITY

Ames test: Negative

Chromosomal aberration test: Negative

Trisphenol derivative:

ACUTE TOXICITY

Oral LD50 Rat >5,000 mg/kg

MUTAGENICITY

Ames test: Negative

Melamine compound:

ACUTE TOXICITY

Oral LD50 Rat 1,800 mg/kg

Photosensitizer: No information available

Phenolic resin: No information available

CARCINOGENICITY:

Not known to be carcinogenic.

NTP: No, IARC MONOGRAPHS: No, OSHA Regulated: No

For potential routes of exposure, symptoms related to the toxicological characteristics, delayed and immediate effects and chronic effects from short and long-term exposure see Section 4 on this SDS.

12. ECOLOGICAL INFORMATION

SOLVENT (MMP):

Eco toxicity: [Estimated by ECOSAR]

Fish: LC50 96hr 196 mg/L (Fish)

Crustacean: EC50 48hr 515 mg/L (Daphnia magna)

Algae: EC50 72 or 96hr 269 mg/L (Green Algae)

Trisphenol derivative:

Eco toxicity:

Fish: LC50 96hr >100 mg/L (Oryzias latipes)

Crustacean: EC50 48hr >100 mg/L (Daphnia magna)

Algae: EC50 72 or 96hr >100 mg/L (Pseudokirchneriella subcapitata)

Melamine compound:

No information available

Photosensitizer:

No information available

PRODUCT NAME: **JSR NFR016D2-55cP**

Phenolic resin: No information available

13. DISPOSAL CONSIDERATION

The user of this product must properly characterize the waste generated from the use of this product in accordance with all applicable federal, state and/or local laws and regulations in order to determine the proper disposal of the waste in accordance with all applicable federal, state and/or local laws and regulations.

14. TRANSPORT INFORMATION

TRANSPORTATION AND HAZARDOUS MATERIALS DESCRIPTION:

Package and transport in accordance with Department of Transportation (DOT) and other regulatory agency requirements.

U. S. DOT PROPER SHIPPING NAME: UN1866, Resin solution, Class 3, III
IATA PROPER SHIPPING NAME: Resin solution
IDENTIFICATION NUMBER: UN1866

15. REGULATORY INFORMATION

US

OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200: Ensure that the hazards associated with this product are transmitted to employees by means of a hazard communications program, in accordance with federal and state Occupational Safety and Health Administration (OSHA) regulations.

CERCLA/SUPERFUND HAZARD CATEGORY: At the time of this document's preparation, none of the ingredients of this product were listed in 40 CFR 302.4. The list should be periodically checked for applicable updates.

SARA 313 INFORMATION: At the time of this document's preparation, none of the ingredients of this product were listed in 40 CFR 372. The list should be periodically checked for applicable updates.

TOXIC SUBSTANCES CONTROL ACT (TSCA): All of the compounds in this product are on the TSCA Inventory and/or are subject to a Low Volume Exemption. The Trisphenol derivative is subject to the significant new use rule (40 CFR 721.5867). In accordance with federal regulations, this material shall be used only to industrially manufacture integrated circuits. In particular, this material shall not be distributed to any person, other than for disposal, until after it has been completely reacted. All users must utilize the worker protection measures and environmental release controls specified in this Safety Data Sheet and in EPA and OSHA regulations. The significant new use rule codified in 40 CFR 721.5867 should be reviewed to ensure hazard communication programs, workplace practices and recordkeeping meet federal requirements. Use of this product without implementing the programs specified in 40 CFR 721.5867 shall be considered a significant new use. Acknowledgment of receipt of this Safety Data Sheet shall be considered acknowledgement that the user will comply with these requirements.

CALIFORNIA PROPOSITION 65 WARNING: At the time of this document's preparation, one or more constituents of this product were included on the California Proposition 65 list of chemicals known to cause cancer and birth defects or other reproductive harm. The list should be periodically checked for applicable updates.

PRODUCT NAME: **JSR NFR016D2-55cP**

16. OTHER INFORMATION

REVISION SUMMARY

May 28, 2015

Original SDS established.

To the best of our knowledge, the information contained herein is accurate. However, neither JSR Corporation nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards, which exist.